




Recessed Lunar T5

cryselco.co.uk/lnr

All fittings in this new range exceed the requirements of Building Regulation L2 revised October 2010. The requirement is an efficacy of 55 lumens per circuit watt and these fittings are substantially better than this requirement, some achieving over 83 lumens per circuit watt. Please contact us if you need any further information on this matter.

Very high performance T5 Direct/Indirect recessed fittings available with polished specular louvres or micro prismatic panels. Satin (semi-specular) louvres are also available to special order. The standard version is a lay-in but plaster board and limited surface formats may be possible to produce – please enquire. 1195mm x 595mm versions are available to special order.

Emergency - Emergency conversion available.



Single Louvre				
Cat. No.	Lamps Req	A	B	C
LNR/66/114/SINGLE LVR/PAR	1 x 14w T5	595	595	100
LNR/66/124/SINGLE LVR/PAR	1 x 24w T5	595	595	100
LNR/66/214/SINGLE LVR/PAR	2 x 14w T5	595	595	100
LNR/66/224/SINGLE LVR/PAR	2 x 24w T5	595	595	100
Twin Louvre				
Cat. No.	Lamps Req	A	B	C
LNR/66/214/TWIN LVR/PAR	2 x 14w T5	595	595	100
LNR/66/224/TWIN LVR/PAR	2 x 24w T5	595	595	100
LNR/66/414/TWIN LVR/PAR	4 x 14w T5	595	595	100
LNR/66/424/TWIN LVR/PAR	4 x 24w T5	595	595	100
Triple Louvre				
Cat. No.	Lamps Req	A	B	C
LNR/66/314/TRIPLE LVR/PAR	3 x 14w T5	595	595	100
LNR/66/324/TRIPLE LVR/PAR	3 x 24w T5	595	595	100
LNR/66/614/TRIPLE LVR/PAR	6 x 14w T5	595	595	100
LNR/66/624/TRIPLE LVR/PAR	6 x 24w T5	595	595	100
Duo Louvre				
Cat. No.	Lamps Req	A	B	C
LNR/66/214/DUO LVR/PAR	2 x 14w T5	595	595	100
LNR/66/224/DUO LVR/PAR	2 x 24w T5	595	595	100
LNR/66/414/DUO LVR/PAR	4 x 14w T5	595	595	100
LNR/66/424/DUO LVR/PAR	4 x 24w T5	595	595	100
Single Micro Prism Panel				
Cat. No.	Lamps Req.	A	B	C
LNR/66/114/1 M PRIS.DIF	1 x 14w T5	595	595	100
LNR/66/124/1 M PRIS.DIF	1 x 24w T5	595	595	100
LNR/66/214/1 M PRIS.DIF	2 x 14w T5	595	595	100
LNR/66/224/1 M PRIS.DIF	2 x 24w T5	595	595	100
Duo Micro Prism Panel				
Cat. No.	Lamps Req.	A	B	C
LNR/66/214/DUO M PRIS.DIF	2 x 14w T5	595	595	100
LNR/66/224/DUO M PRIS.DIF	2 x 24w T5	595	595	100
LNR/66/414/DUO M PRIS.DIF	4 x 14w T5	595	595	100
LNR/66/424/DUO M PRIS.DIF	4 x 24w T5	595	595	100

600 x 1200 versions to special order

Control Gear options
 Digital SwitchDIM dimming, Analogue 1 to 10 volt dimming, DSI and DALI,
 Control gear is HF as standard.